

All fires, fast.




FIREXO SMALL EXTINGUISHER

Name	Firexo Small 0.1g Extinguisher
Firexo Model #	809-765-347-816
EAN Barcode #	5060638820017
Capacity	0.1 gallons
Cylinder Height	11.4 inches
Outer Diameter	2.6 inches
Cylinder Material	Stainless Steel
Pressurizing Gas	Nitrogen
Test Pressure	435 PSI / 30 BAR
Operating Pressure	145 PSI / 10 BAR
Weight Full (unit only / boxed, with bracket)	2.43 pounds / 3.05 pounds
Weight Empty	1.8 pounds
Spray Range	3 - 10 feet
Discharge Time at 68°F	5 - 6 seconds
Operating Temperature Range (°F / °C)	+10.4°F to +120°F / -12°C to +49°C
Warranty	5 years
Fire Class	A / B / C / D / K
Gas & Liquid Gas Tested	Yes
CE Approval	CE 0036



All fires, fast.



METHOD OF USE

Discharge all contents onto the fire from approximately 10 feet. The extinguisher should be installed, inspected, maintained and recharged in accordance with NFPA 10 (where applicable) and the manufacturers recommendations. When tested and certified to European EN3-7 this Firexo fire extinguisher has achieved the following fire test ratings; 3A/13B/C/D/E/5F. Tested to 35KV and safe to use on live electrical equipment at 1,000v at a distance of 3 feet. Tested on magnesium fires. It is recommended that potential fires involving specialist metals should be subject to a fire risk assessment. Tested on gas fires. It is recommended that fires involving flammable gases are dealt with by professional fire-fighting departments. See website for further details.

Call +1 419-573-6001

© FIREXO 2020

This data specification sheet provides guidance only. It does not represent scientific or professional advice to any recipient or third party reader. Whilst great care has been taken to compile accurate data herein, FIREXO does not accept any responsibility or legal liability for any errors or omissions.

firexo

firexo.com