

FIREXO 500ml AEROSOL

Name	Firexo 500ml Aerosol
Model/Product number	809-765-347-816
Capacity (litres)	0.5
Overall Product Height (mm)	290
Cylinder Height (mm)	265
Cylinder Diameter (mm)	63
Cylinder Material	Stainless Steel
Pressurizing Gas	Nitrogen
Test Pressure (bar)	27 bar
Working Pressure at 20 °C	12 bar
Weight Full (kg) Unit Only / boxed, with bracket	1.1 / 1.35
Weight Empty (kg)	0.53
Spray Range (m)	1 – 3
Discharge Time at 20 °C (seconds)	10 – 12
Temperature Range (°C)	-15°C / +60°C
Warranty	3yr
Fire Rating	3A/13B /C/D/Electrical/5F



3

ALL FIRES.



METHOD OF USE

In the event of a fire hold aerosol upright, pull out safety pin, aim at base of fire, squeeze handle and sweep side to side.

Discharge entire contents onto the fire from at least a 1m distance.

Replace after use.

Tested on electrical to 35 kV.

Warning - Keep out of reach of children - Do not pierce or burn, even after use.

© FIREXO 2022

This data specification sheet provides guidance only. It does not represent scientific or professional advice to any recipient or third party reader. Whilst great care has been taken to compile accurate data herein, FIREXO does not accept any responsibility or legal liability for any errors or omissions.