

FIREXO 9LTR STAINLESS STEEL EXTINGUISHER

| Name | Firexo 9LTR Extinguisher |
|-----------------------------------|--------------------------|
| Model/Product number | 809-765-347-126 |
| Capacity (litres) | 9 |
| Vessel Overall Height (mm) | 637 |
| Outer Width (mm) | 180 |
| Cylinder Material | SUS 304 |
| Pressurizing Gas | Nitrogen |
| Test Pressure (bar) | 30 bar |
| Working Pressure at 20 °C | 12 bar |
| Weight Full (kg) | 14.1 |
| Weight Empty (kg) | 3.75 |
| Spray Range (m) | 1 – 4 |
| Discharge Time at 20 °C (seconds) | 35 – 40 |
| Temperature Range (°C) | -15°C / +60°C |
| Warranty | 5yr |
| Fire Rating | 55A/183B/C/D/E/75F |
| CE Approval | CE 0036 |



ALL FIRES.



METHOD OF USE

In the event of a fire hold extinguisher upright, pull out safety pin, aim at base of fire, squeeze handle and sweep side to side.

Discharge entire contents onto the fire from a 1m-3m distance.

It is recommended to use the extinguisher from a safe distance.

It should be replaced or recharged after use.

Tested to 35 kV for electrical fires thus suitable for use on live electrical equipment up to 1000 V at a distance of 1m.

© FIREXO 2022

This data specification sheet provides guidance only. It does not represent scientific or professional advice to any recipient or third party reader. Whilst great care has been taken to compile accurate data herein, FIREXO does not accept any responsibility or legal liability for any errors or omissions.