KM 781168
BS EN 3-7:2004+A1:2007

# PRODUCT INFORMATION

## Firexo 2L All Fires Extinguisher




PFAS FREE

| Product | Firexo 2L ALL FIRES |
|---|---|
| Model/product no. | 809-765-347-846 |
| Capacity | 2 litres |
| Product height | 415 mm |
| Cylinder height | 313 mm |
| Cylinder diameter | 110 mm |
| Cylinder material | Steel |
| Pressurising gas | Nitrogen |
| Extinguishing agent | fx51 Firexo ALL FIRES Extinguishing Agent |
| Test pressure | 30 bar |
| Working pressure | 12 bar |
| Weight (full) | 4.09 kg |
| Weight (empty) | 1.75 kg |
| Spray range | 1-3 m |
| Discharge time | 20-25 seconds |
| Temperature range | -15 °C / +60 °C |
| Warranty | 5 years |
| Fire ratings | 13A / 34B / C / D / Electrical / 25F / Lithium-ion |

2797/2026
BSI/MED/3.2/796133

CE
0036

## Method of Use



In the event of a fire hold extinguisher upright, pull out safety pin, aim at base of fire, squeeze handle and sweep side to side. Discharge entire contents onto the fire from a 1-3 m distance.

Store upright and away from direct sunlight or heat source. Protect from frost. Replace or recharge after use.
Tested on electrical equipment fires to 35 kV. Suitable for use on live electrical equipment out to 1000 V at a distance of 1 m.

Firexo 2 L Standard Red ALL FIRES Fire Extinguishers carry the BSI Kitemark and are certified to BS EN 3-7 for classes A, B and F, and for use on electrical fires up to 1000 V.
They are also suitable for use on Class C, D and fires involving lithium-ion batteries, having demonstrated suitability through various in-house and independent third-party testing programmes.




© FIREXO 2026

This data specification sheet provides guidance only.
It does not represent scientific or professional advice to any recipient or third party reader.
Whilst great care has been taken to compile accurate data herein, Firexo does not accept any responsibility or legal liability for any errors or omissions.

V. OCT2026