

# PRODUCT INFORMATION

## Firexo 500ml All Fires Aerosol Extinguisher



Product	Firexo 500ml ALL FIRES Aerosol
Model/product no.	809-765-347-816
Capacity	0.5 litres
Product height	295 mm
Cylinder height	235 mm
Cylinder diameter	64 mm
Cylinder material	Stainless Steel
Pressurising gas	Nitrogen
Extinguishing agent	fx51 Firexo ALL FIRES Extinguishing Agent
Test pressure	27 bar
Working pressure	10-12 bar
Weight (full)	1.1 kg
Weight (empty)	0.52 kg
Spray range	1-2 m
Discharge time	8-12 seconds
Temperature range	-15 °C / +60 °C
Warranty	3 years
Approvals	Aerosol Dispense Directive 75/324/EEC, BS 6165:20219
Fire ratings	3A / 13B / C / D / Electrical / 5F / Lithium-ion

### Method of Use



In the event of a fire hold extinguisher upright, pull out safety pin, aim at base of fire, squeeze handle and sweep side to side. Discharge entire contents onto the fire from a 1-3 m distance. Tested on electrical equipment fires to 35 kV.

**WARNING!** Keep out of reach of children. Do not use if tamper or damage is visible - replace immediately. Do not reuse. Do not pierce or burn, even after use. Protect from frost. Store in cool, dry place, away from direct sunlight or heat source. Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F. Pressurised container: may burst if heated. Do not drink.



### © FIREXO 2026

This data specification sheet provides guidance only. It does not represent scientific or professional advice to any recipient or third party reader. Whilst great care has been taken to compile accurate data herein, Firexo does not accept any responsibility or legal liability for any errors or omissions.

V. JUL2026

**ADD** 3  
Aerosol Dispense Directive  
75/324/EEC