# PRODUCT INFORMATION

## Firexo 500ml All Fires Aerosol Extinguisher




PFAS FREE

| Product | Firexo 500ml ALL FIRES Aerosol |
|---|---|
| Model/product no. | 809-765-347-816 |
| Capacity | 0.5 litres |
| Product height | 295 mm |
| Cylinder height | 235 mm |
| Cylinder diameter | 64 mm |
| Cylinder material | Stainless Steel |
| Pressurising gas | Nitrogen |
| Extinguishing agent | fx51 Firexo ALL FIRES Extinguishing Agent |
| Test pressure | 27 bar |
| Working pressure | 10-12 bar |
| Weight (full) | 1.1 kg |
| Weight (empty) | 0.52 kg |
| Spray range | 1-2 m |
| Discharge time | 8-12 seconds |
| Temperature range | -15 °C / +60 °C |
| Warranty | 3 years |
| Approvals | Aerosol Dispense Directive 75/324/EEC, BS 6165:20219 |
| Fire ratings | 3A / 13B / C / D / Electrical / 5F / Lithium-ion |

ADD
Aerosol Dispense Directive
75/324/EEC
3

## Method of Use



In the event of a fire hold extinguisher upright, pull out safety pin, aim at base of fire, squeeze handle and sweep side to side. Discharge entire contents onto the fire from a 1-3 m distance. Tested on electrical equipment fires to 35 kV.

WARNING! Keep out of reach of children. Do not use if tamper or damage is visible - replace immediately. Do not reuse.
Do not pierce or burn, even after use. Protect from frost.
Store in cool, dry place, away from direct sunlight or heat source. Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F. Pressurised container: may burst if heated.
Do not drink.




© FIREXO 2026

This data specification sheet provides guidance only.
It does not represent scientific or professional advice to any recipient or third party reader. Whilst great care has been taken to compile accurate data herein, Firexo does not accept any responsibility or legal liability for any errors or omissions.

V. OCT2026