

PRODUCT INFORMATION

Firexo 6L All Fires Extinguisher Stainless Steel



Product	Firexo 6L ALL FIRES Stainless Steel
Model/product no.	809-765-347-096
Capacity	6 litres
Product height	530 mm
Cylinder height	450 mm
Cylinder diameter	162 mm
Cylinder material	Stainless Steel
Pressurising gas	Nitrogen
Extinguishing agent	fx51 Firexo ALL FIRES Extinguishing Agent
Test pressure	30 bar
Working pressure	12 bar
Weight (full)	9.50 kg
Weight (empty)	2.48 kg
Spray range	1-4 m
Discharge time	25-30 seconds
Temperature range	-15 °C / +60 °C
Warranty	5 years
Fire ratings	34A / 113B / C / D / Electrical / 75F / Lithium-ion

Method of Use



In the event of a fire hold extinguisher upright, pull out safety pin, aim at base of fire, squeeze handle and sweep side to side. Discharge entire contents onto the fire from a 1-4 m distance. Store upright and away from direct sunlight or heat source. Protect from frost. Replace or recharge after use. Tested on electrical equipment fires to 35 kV.



© FIREXO 2026

This data specification sheet provides guidance only. It does not represent scientific or professional advice to any recipient or third party reader. Whilst great care has been taken to compile accurate data herein, Firexo does not accept any responsibility or legal liability for any errors or omissions.

V. SEP2026