Portable Fire Extinguisher KITEMARK™
KM 781168
BS EN 3-7:2004+A1:2007

PRODUCT INFORMATION

Firexo 6L All Fires Extinguisher



PFAS FREE

Product	Firexo 6L ALL FIRES
Model/product no.	809-765-347-876
Capacity	6 litres
Product height	520 mm
Cylinder height	430 mm
Cylinder diameter	162 mm
Cylinder material	Steel
Pressurising gas	Nitrogen
Extinguishing agent	fx51 Firexo ALL FIRES Extinguishing Agent
Test pressure	30 bar
Working pressure	12 bar
Weight (full)	10.67 kg
Weight (empty)	3.65 kg
Spray range	1-4 m
Discharge time	25-35 seconds
Temperature range	-15 °C / +60 °C
Warranty	5 years
Fire ratings	34A / 113B / C / D / Electrical / 75F / Lithium-ion

2797/2026
BSI/MED/3.2/796133

CE 0036

Method of Use



In the event of a fire hold extinguisher upright, pull out safety pin, aim at base of fire, squeeze handle and sweep side to side. Discharge entire contents onto the fire from a 1-4 m distance.

Store upright and away from direct sunlight or heat source. Protect from frost. Replace or recharge after use.
Tested on electrical equipment fires to 35 kV. Suitable for use on live electrical equipment out to 1000 V at a distance of 1 m.

Firexo 6 L Standard Red ALL FIRES Fire Extinguishers carry the BSI Kitemark and are certified to BS EN 3-7 for classes A, B and F, and for use on electrical fires up to 1000 V.
They are also suitable for use on Class C, D and fires involving lithium-ion batteries, having demonstrated suitability through various in-house and independent third-party testing programmes.



© FIREXO 2026

This data specification sheet provides guidance only.
It does not represent scientific or professional advice to any recipient or third party reader.
Whilst great care has been taken to compile accurate data herein, Firexo does not accept any responsibility or legal liability for any errors or omissions.

V. OCT2026